

On Extended Simple Eco-grammar Systems

Judit Csima

The concept of the eco-grammar system (the *EG* system, for short) has been introduced in [3] as a model of communities of agents which interact with their common shared environment. Several aspects of these systems were discussed in [4] and [7], properties of a restricted variant, called simple eco-grammar systems, were studied in [5], [1], [9], [2], [6], and [8]. Briefly, a simple eco-grammar system consists of several agents (represented by sets of context-free rules) and an environment (given by a set of *0L* rules). At any moment of time, the behaviour of the system is described by the state of the environment which is a string over the alphabet of the system. The environmental state changes by derivation steps. In a derivation step the agents act on the string by applying one of their context-free rules - each agent rewrites only one letter - and the environment replaces, according to its *0L* rule set, in a parallel manner the symbols where the agents do not perform any action.

Starting from an initial string representing the environment, a lot of sequences of strings following each other arise which describe the evolving system. The language generated by the eco-grammar system is the set of strings which can be obtained from the initial environmental state by a sequence of derivation steps. In the case of extended simple eco-grammar systems only those strings belong to the determined language which are over a distinguished subset of the alphabet of the system, the terminal alphabet. This notion was introduced and some basic properties were examined in [6].

Following that line, in this contribution we deal with a more sophisticated version of the derivation, the team behaviour of the extended simple eco-grammar systems: in each derivation step from the n agents exactly k or at most k have to perform an action. We describe the behaviour and the generative power of these systems according to some size parameters: the total number of agents, the number of agents being active in a derivation step. We examine the hierarchy of the language classes generated by extended simple eco-grammar systems with and without λ -rules.

The results demonstrate that while in the non-extended case the size parameters of the teams and the agent population have influence on the power of the system, in the extended case these parameters are not important: we obtain a collapsing hierarchy.

References

- [1] J. Csima. Formal language theoretic models of ecosystems (In Hungarian). Master's thesis, ELTE, Budapest, 1997.
- [2] J. Csima and E. Csuhaj-Varjú. Eco-rewriting systems: components with insertions and replacements. Manuscript, 1998.
- [3] E. Csuhaj-Varjú, J. Kelemen, A. Kelemenová, and Gh. Păun. Eco(-grammar) systems. A preview. In R. Trappl, editor, *Proc 12th European Meeting on Cybernetics and System Research*, pages 941–948. World Sci. Publ., Singapore, 1994.
- [4] E. Csuhaj-Varjú, J. Kelemen, A. Kelemenová, and Gh. Păun. A grammatical approach to lifelike interactions. *Artificial Life*, 3:1–28, 1997.
- [5] E. Csuhaj-Varjú and A. Kelemenová. Team behaviour in simple eco-grammar systems. Theoretical Computer Science, to appear.
- [6] J. Dassow and V. Mihalache. Eco-grammar systems, matrix grammars and E0L systems. In Gh. Păun, editor, *Artificial Life: grammatical models*, pages 210–226. Black Sea Univ. Press, Bucharest, 1995.
- [7] Gh. Păun, editor. *Artificial Life: grammatical models*. Black Sea Univ. Press, Bucharest, 1995.

- [8] M. H. ter Beek. Teams in grammar systems. Master's thesis, Leiden University, Leiden, 1996.
- [9] M. H. ter Beek. Teams in grammar systems: Hybridity and weak rewriting. *Acta Cybernetica*, 12(4):427–444, 1996.